

GasAlert MaxXT II



GasAlertMax XT II is the smart, simple, economical way to compliance. With its built-in motorised sampling pump, GasAlertMax XT II reliably monitors up to four gas hazards (H₂S, CO, O₂ and combustible gases).

Customise your detector to suit your specific needs.

Confined Space Kits



Deluxe Confined Space Kit

The Deluxe Confined Space Kit (XT-CK-DL) comes equipped with: concussion-proof boot, carrying holster, IR Connectivity Kit, 0.5 LPM regulator, 3 ft. / 1 m calibration hose with quick connect, 10 ft. / 3 m sampling hose with quick connect, sampling probe, and hard-sided carrying case with lid insert pockets and foam case insert. Detector and calibration gas sold separately.

Confined Space Kit Carrying Case

The durable, compact Carrying Case (XT-CK-CC, not pictured) conveniently holds your gas detector kit and everything you need for safe sampling in confined space entry work.

Carrying Accessories



GA-BXT

Concussion-Proof Boot

The external rubber boot keeps detectors cleaner and provides an additional level of protection in extreme conditions. The boot fits securely onto the detector and is equipped with a rugged stainless steel, alligator-style clip.



GA-HXT

Carrying Holster

Securely attach the GasAlertMax XT II and tubing to your belt with the durable Carrying Holster.



GA-NS-1

Neck strap with Safety Release

Wear the detector close to the breathing zone without hampering mobility. In the event the strap becomes caught, the safety release will break away from the Neck Strap.



GA-LY-1

Short Strap

The Short Strap (6 in. / 15.2 cm) facilitates the attachment of your gas detector to your clothing or personal protective equipment (PPE). The smaller loop attaches to buttons or other fasteners.



GA-ES-1

Extension Strap

The 4 ft. / 1.2 m extension strap attaches easily to the detector.

Carrying Accessories (con't)



GA-CH-2

Chest Harness

Keep the detector secure to your chest and close to the breathing zone. Mobility is not hampered with the Chest Harness. The harness is secured around the user's shoulders and torso.



GA-ARM-1

Arm Band

Comfortably secure the detector to your arm with the Arm Band accessory to ensure it is worn close to the breathing zone without hampering mobility. The alligator clip on the detector attaches easily to the Arm Band.

Power Accessories



XT-C01-MC5

Multi-Unit Cradle Charger

Simultaneously charge 5 detectors with the Multi-Unit Cradle Charger. Simply slip detectors into the charger and wait for the battery icon on the LCD to indicate the battery is fully charged.



GA-PA-1-MC5-NA *

Multi-Unit Power Adaptor

Simultaneously charge 5 detectors with the Multi-Unit Power Adaptor. Simply connect each adaptor to a detector's charging/IR interface and wait for the battery icon on the LCD to indicate the battery is fully charged.



GA-VPA-1

Vehicle Power Adaptor

Charge your detector easily anywhere you go with the Vehicle Power Adaptor. Suitable for 12V applications. Simply connect the adaptor to the detector's charging/IR interface and charging port and wait for the battery icon on the LCD to indicate the battery is fully charged.



GA-PA-3

12-24 Vdc Direct-Wire Power Adaptor

Connect directly to a 12V or 24V power system with the 12-24 Vdc Direct-Wire Power Adaptor. Simply connect the adaptor to the detector's charging/IR interface.



GA-PA-1-NA *

Replacement Power Adaptor

Ensure your detector is charged and ready for use with the IR power adaptor. Simply connect the adaptor to the detector's charging/IR interface and wait for the battery icon on the LCD to indicate the battery is fully charged. Included with detector.

Miscellaneous Accessories



GA-USB1-IR **IR Connectivity Kit**

The IR Connectivity Kit easily connects to the IR communications and charging port, linking your detector to your computer for data downloads and access to instrument set-up options.



Fleet Manager II

Fleet Manager II enables users to download information directly from the GasAlertMax XT II detector or the MicroDock II system. Data storage and analysis is made easy. Fleet Manager II also enables users to customise user-definable detector options. Included with IR Connectivity Kit.

Sampling/ Testing Accessories



MicroDock II

The MicroDock II is the cost-effective way to manage the GasAlertMax XT II. Calibration, bump testing, charging and record keeping are simplified. Fully portable, the MicroDock II requires no computer and can manage up to 6 GasAlertMax XT II docking modules.



GA-PROB1-1

Sample Probe

The Sample Probe (1 ft. / 0.3 m) is ideal for pick hole sampling or sampling hard to reach places. The particulate filters and hydrophobic barrier prevents moisture and debris from entering the detector.



GA-PROB-FIL-K1

Filter and Gaskets Replacements for GA-PROB1-1

Replacement Hydrophobic Filters (1.0 μ m), Particulate Filters and Gaskets for use with the Sample Probe to prevent moisture and particulates from entering the detector.



M0931K

Quick-Connect Fitting Spares for Sampling Hose

Attaching the tubing to the pump inlet is easy with Quick-Connect fitting. The Quick-Connect fitting spares come in a kit of 2.



GA-CPROB1 / GA-CPROB2

Collapsible Sample Probe with Handle

The Collapsible Sample Probe with Handle is ideal for pick hole sampling and sampling hard to reach places. Comes in 3.3 ft. / 1 m or 6 ft. / 1.8 m lengths.



D4-PROB1 / D4-PROB3 / D4-PROB6

Search Probe with Handle and Quick Connect

Sample remote locations with the Search Probe with Handle and Quick Connect. Attaching the tubing to the pump inlet is easy with Quick Connect fitting. Comes in 1 ft. / 0.3 m, 3 ft. / 0.9 m, or 6 ft. / 1.8 m lengths.

Sampling/ Testing Accessories (con't)**GA-FLOAT****Sampling Float**

For obtaining samples directly above liquids, the Sampling Float is the easy solution. The hose connects to an axel between two buoys. The inlet is elevated above the liquid surface.

**GA-MFILTER****Metallic Sintered Particulate Filter**

The Metallic Sintered Particulate Filter prevents dirt and debris from entering and clogging the pump.

**M5-AF-K2 / M5-AF-K2-100****Auxiliary Filter for GasAlertMax XT II Pump**

For extremely high dust environments. The Auxiliary Filter provides extra protection for the pump. Available in a kit of 5 or 100.

**XT-RF-H5 / XT-RF-H50 / XT-RF-H100****Hydrophobic Filter Replacement for GasAlertMax XT II Pump**

The Hydrophobic Filter Replacement can be easily inserted into the GasAlertMax XT II to prevent moisture from entering the detector. Comes in kits of 5, 50 or 100.

**GA-PFMAX / GA-PFMAX-50 / GA-PFMAX-100****Particulate Filter Replacement for GasAlertMax XT II Pump**

The Pump Particulate Filter, available in kits of 5, 50 and 100, can be easily replaced when filters in use become dirty or clogged.

**Calibration/Test Equipment**

A range of 7L, 34L, 58L, 103L and 900L test gas cylinders and kits are available. Calibration is only as accurate as the test gas used, therefore BW Technologies by Honeywell test gases are made to N.I.S.T. (National Institute of Standards and Technology) standards.

European Headquarters

4 Stinsford Road
Nuffield Industrial Estate
Poole, Dorset BH17 0RZ
United Kingdom
tel +44 (0) 1295.700.300
fax +44 (0) 1295.700.301

www.gasmonitors.com

Europe	+44 (0) 1295.700.300
France	+33 (0) 442.98.17.70
Germany	+49 (0) 2137.17.6522
Middle East	+971.4.4505852
USA	1.888.749.8878

bwesales@gasmonitors.com

Latin America	+55.11.3475.1873
S.E. Asia	+65.6580.3468
China	+86.10.6786.7305
Australia	+61.3.9464.2770
Other Countries	+1.403.248.9226