

# FIXED VOC MONITOR



# Unrivalled Gas Detection.





# CONTINUOUS DETECTION OF VOLATILE ORGANIC COMPOUNDS (VOCs) WITH MULTIPLE RANGE FROM JUST ONE INSTRUMENT.

## Best available photoionisation (PID) detection


- PID independently verified as best performing on the market
- Range: 0 to 10, 0 to 100 or 0 to 1000 ppm from just one instrument
- In-built humidity resistance with no need to compensate
- Anti-contamination design for extended field operation
- Reliable diffusive monitoring - no pump required
- An optional sensor cap allows a pipe connection

## Safety

- Accurate results over all environmental conditions
- Rugged and robust design withstands harsh environments
- Large LCD display for clear readings
- ATEX and IECEx approved

## Ease of use

- Simple to use - minimal training required
- Easy access PID sensor for fast, simple servicing
- Simple calibration procedure
- Easily integrated into a control system



## Low cost operation

- Inexpensive consumables and parts
- 2 year warranty when instrument is registered online



MiniPID 2 sensor



TVOC 2 is a fixed photoionisation detector (PID) for the continuous measurement of total volatile organic compounds (VOCs). TVOC 2 can accurately measure three detection ranges.

TVOC 2 continually measures and updates the output every second.

TVOC 2 utilises a diffusive sample technique resulting in less contamination issues compared to pumped systems, reducing lamp cleaning and servicing requirements. The 4-20 mA analogue output enables TVOC to be integrated into a DCS control system to give warning or control of high VOC levels in the working environment.

ATEX approvals enable a 3 wire TVOC system to be used in Zone 2 hazardous areas, without safety barriers. ATEX and IECEx approvals allow TVOC to be used in Zone 1 hazardous areas, with safety barriers.

Simple to install, service and calibrate, TVOC 2 requires no hot work permit and the PID sensor is accessible and changeable in a matter of seconds.

### Extend your instrument warranty

Your TVOC 2 instrument warranty may be extended by simply registering your product on the Ion Science website within one month of purchase. Visit [www.ionscience.com/instrument-registration](http://www.ionscience.com/instrument-registration) to take advantage of this offer.

### Applications include:

- Manufacturing
- Processing
- Offshore
- Refineries & petrochemical
- Chemical
- Waste water treatment
- Pulp & paper
- Pharmaceutical
- Indoor air quality
- Solvent recovery systems
- Industrial painting & coating

### Accessories

TVOC 2 is supplied with an exclusive range of accessories. Visit [www.ionscience.com/tvoc](http://www.ionscience.com/tvoc) for more info.



## Technical specifications

### Approvals

- II 2G Ex ia IIC T4 Gb  
(-20°C ≤ Ta ≤ +50°C)
- II 3G Ex nA IIC T4  
(-40°C ≤ Ta ≤ +50°C)
- Baseefa05ATEX0277X
- IECEx BAS 06.0057X

### Ingress protection rating

- Designed to IP65
- Sensor Ingress Protection IP54

### Power

- 5-28 VDC Max 130 mA

### Output

- 4-20 mA requires a 8-35 VDC power supply
- For IS requirements 8-30 VDC power supply

### Range

- 0 to 10 ppm, 0 to 100 ppm, 0 to 1000 ppm (user selectable)

### Sampling

- Diffusion (can be pumped if required using an adaptor)

### Display

- 7 segment, 4 digit LCD, 4 color LEDs

### Response

- Sensor - T90 < 5 sec

### Accuracy

- 0 to 100 ppm: ± 5% at calibration point.  
100 to 1000 ppm: ± 10% at calibration points.

### Calibration

- Accessed via magnetic switch
- 100 ppm Isobutylene via calibration kit accessory

### Temperature

- Operating: -20 °C to 50 °C (-4 °C- 122 °F)
- Humidity: 0-95% RH (non- condensing)

### Weight & dimensions

- Instrument: 1.4 kg (3.1 lb)  
Packed: 1.6 kg (3.5 lb)
- Dimensions: 188 x 126 x 78 mm (7.4 x 4.9 x 3")

### 4-20 mA alarm levels

- Selectable 2 mA & 3.5 mA options

TVOC 2 V1.0 This publication is not intended to form the basis of a contract and specifications can change without notice.

All specifications quoted are at calibration point and under the same ambient conditions. Specifications are based on isobutylene calibration at 20 °C and 1000 mBar.

\* The Fence Electrode technology referred to in this document is produced by Ion Science Ltd, and protected by patents. U.S. Patent No. 7,046,012. EP 1474681, other patents pending. TVOC 2 is a registered trademark of Ion Science Ltd.

## Distributed by:

### ION Science Ltd

The Hive, Butts Lane,  
Fowlmere, Cambridgeshire,  
SG8 7SL, UK

T +44 (0)1763 208503  
E [info@ionscience.com](mailto:info@ionscience.com)



Afriso Ema AB  
Kilvägen 2  
SE-232 37 Arlöv  
[www.afriso.se](http://www.afriso.se)

040-92 20 50  
[info@afriiso.se](mailto:info@afriiso.se)

Order:  
040-92 20 57  
[order@afriiso.se](mailto:order@afriiso.se)

Service:  
040-92 20 53  
[service@afriiso.se](mailto:service@afriiso.se)